



PRODUCT SELECTION CONSIDERATIONS

- **WHAT IS THE SUBSTRATE?**
- **WHAT IS THE VENEER?**
- **WHAT ARE THE CONDITIONS?**

PRODUCTS:

VBM - High bond strengths, non-sag, and efflorescence resistance

VBM 300 - Added flexural bond and water repellent properties. OK for wet or submerged areas.

VBM 500 - Best flexural bond, water repellent, and efflorescence protection. Best for submerged applications.

ACCESSORY PRODUCTS - PROBLEM SOLVERS

R-AcrylicAd - Add to bonding and grouting mortar. Adds flexural strength and water repellency. **UV Stable**. Improves polymer modification of mortars for more demanding jobs.

R-Lastic- Liquid applied waterproofing and bonding agent. Will bond to glass and metal.

Application Conditions for Product Selection

<u>Light Duty</u> Residential - Low Traffic	<u>Medium Duty</u> Drystack - Large Format	<u>Heavy Duty</u> Commercial - Industrial	<u>X-Heavy Duty</u> Commercial - Vehicle Traffic
- All VBM Mortars	- VBM 300 - VBM 500	- VBM 300 - VBM 500	- VBM 500* * 50-100% mix water replacement with R-AcrylicAd

Coverage: Can vary based on job conditions

1/2" x 1/2" x 1/2" (13x13x13mm)	35-40 Sqft
1/2" Full Coverage (Masonry Veneer)	~15-20 Sqft

Base Use Recommendations¹

	VBM	VBM 300	VBM 500
Manufactured Stone	●	●	●
Natural Stone	●	●	●
Thin Brick	●	●	●
Drystack & Large Format		●	●
Pavers		●	●
Porcelain			●
Wet Areas	●	●	●
Submerged		●	●

*Basic recommendations only. Some variation may occur based on job conditions, veneer type, and application practices.